



SMAC, manual version



CONTACT :
TIFLEX
CS 30200 - 01450 PONCIN France
Tel : +33 (0)4 74 37 33 80/97
Fax : +33 (0)4 74 37 33 62
international@tiflex.fr

Scan this code
and discover
our website!



www.tiflex.com/solutions-gb-mic.html

ROLLERPRINT

Flexographic marking unit with an ink cartridge, Rollerprint is used for continuous printing on all kinds of substrates.

The inks used are compatible with absorbent (paper, carton ...) and non absorbent (iron, plastics...) materials.

It marks the top part of the product.

Its simple functioning warrants a low use cost.



The type drum holder is available in circumference 240 or 375 mm for a printing width 25 mm.

Installation on a production line

ROLLERPRINT is easily installed on a bracket. The type drum is driven by the substrate thanks to two drive types. A pressure regulation improves the contact quality.

Autoclips characters

This system simplifies the changing of the characters. Thanks to the 8 rings, it warrants a perfect adhesion of the message.

Inking

Made to function easily and cleanly, Rollerprint is fed with a liquid fast drying ink.

Tiflex has developed many ink qualities adapted to different kinds of substrates:

- **Ink CP 900** : Adapted to many absorbent or non absorbent substrates.
- **Ink CP 700** : Pigment based with great contrast used for marking on dark substrates.
- **Ink CP 207** : fast drying, adapted to mark on metal, rigid plastics (polyamide), films (treated polyethylene, polyester) paraffined cartons ...
- **Ink FLA 101P and FLA 102C**, adapted to mark on dark coloured PVC.
- **Specific inks** : contact us.

