



# SCREEN PRINTING

## SOLVENT INK

### GLOSSY VINYL

*Glossy air drying ink particularly intended for printing on self-adhesive substrates.*

#### Use

The **GLOSSY VINYL** inks are printed on all varnished vinyl or polyester self-adhesive supports and also on polycarbonate sheets (macrolon®, lexan®).

10% to 30% matting base must be added, depending on the required finish.
















Not suitable on flexible PVC.

#### Specifications

➤ Appearance:	high glossy	➤ Solvents:	
➤ Average density:	1,12	• thinner	4920
➤ Viscosity:	7 ± 1 Pa.s	• drying activator	4905
➤ Drying:		• retarder	4960 or retargel or 9640
• ambient air	15 min. at 20°C	• gun	XC 876
• air jet dryer	1 min. at 50°C	➤ Cleaning solvents:	
➤ Covering power:	good	• manual	2881, 2891, NS-81, NS-91, NS-99 and NS-100
➤ Coverage rate:	50 m²/l with a 120 -34 mesh	• washer	2881, NS-81, NS-91, NS-99 and NS-100
➤ Weather resistance:	good	➤ Expiry date:	refer to the label

## Storage and toxicology

The **GLOSSY VINYL** inks comply with EN 71-3 standard.

	STANDARD COLOURS	Ref. 1 I
	White 8500	3342004
	Covering white 8505	3342006
	Lemon yellow OP	3342002
	Gold yellow OP	3342005
	Orange OP	3342007
	Cherry red OP	3342009
	Carmine red OP	3342013
	Cyclamen 8560	3342028
	Purple / Violet 8570	3342032
	Light blue 8580	3342036
	Primary blue 8590	3342040
	Deep blue 8600	3342044
	Royal blue 8605	3342046
	Medium green OP	3342033
	Deep green OP	3342034
	Brown OP	3342042
	Black 8660	3342068

Non contractual colours and pictures  
On simple request, we can propose you a color panel card displaying accurate shades.



IMP. TIFLEX 01.01.2018 - Non contractual colours and pictures - Only our Web-site is authorised to give real-time information about our inks. Paper notices are considered unwritten and no longer engage our company's responsibility once they are updated on our Web-site. Our responsibility can be engaged only if the customer has based his position on the information published on our Web-site. In all cases, the user should carry out validation tests under his own conditions before using our inks for his production. The safety data sheets are available free at: [www.tiflex.com/fds](http://www.tiflex.com/fds)

**TIFLEX**  
marquer le monde

CS 30200 - 01450 PONCIN - Tél. +33 (0) 4 74 37 33 80/97  
international@tiflex.fr - [www.tiflex.fr](http://www.tiflex.fr)